




**Cablu tractiune inox 7x19 AISI 316****INOX**


Diametru	Greutatea aprox.	Sarcina minima la rupere
		1570 N/mm <sup>2</sup>
mm	kg/100m	kN
1,5	0,86	1,28
2,0	1,5	2,27
2,5	2,3	3,55
3,0	3,5	5,12
4,0	6,1	9,09
5,0	9,6	14,21
6,0	13,8	20,46
7,0	18,7	27,85
8,0	24,3	33,37
10,0	38,1	56,83
12,0	54,8	81,84
14,0	76,4	111,39
16,00	97,4	145,5

**Cablu tractiune inox 6x36 IWRC AISI 316**
**INOX**


Diametru	Greutatea aprox.	Sarcina minima la rupere
		1570 N/mm <sup>2</sup>
mm	kg/100m	kN
8	24	35,77
10	38	55,89
12	55	80,48
14	75	109,55
16	97	143,08
18	123	181,09
20	152	223,57
22	282	270,52
24	240	322,0
26	282	377,83

**Cablu tractiune inox 7x7 AISI 316**
**INOX**


Diametru	Greutatea aprox.	Sarcina minima la rupere
		1570 N/mm <sup>2</sup>
mm	kg/100m	kN
0,54	0,12	0,16
0,68	0,18	0,26
0,72	0,21	0,29
0,81	0,26	0,37
1,00	0,40	0,56
1,25	0,50	0,88
1,35	0,72	1,03
1,50	0,90	1,27
1,80	1,30	1,83
2,00	1,60	2,25
2,50	2,50	3,52
3,00	3,50	5,07
3,50	4,82	6,90
4,00	6,30	9,02
5,00	9,80	14,09
6,00	14,2	20,29
7,00	19,3	27,62
8,00	25,2	36,07
10,00	39,3	56,36
12,00	56,6	81,00

**Cablu tractiune inox 1x19 AISI 316**
**INOX**


Diametru	Greutatea aprox.	Sarcina minima la rupere
		1570 N/mm <sup>2</sup>
mm	kg/100m	kN
0,54	0,10	0,24
1,00	0,50	0,82
1,25	0,70	1,29
1,50	1,10	1,86
1,80	1,6	2,67
2,00	2,00	3,30
2,50	3,10	5,15
3,00	4,50	7,42
3,50	6,10	10,10
4,00	8,00	13,19
5,00	12,40	20,62
6,00	17,8	29,69
7,00	24,3	40,41
8,00	31,7	52,78
10,00	49,5	78,79
12,00	71,3	109,68
14,00	97,1	137,96
16,00	127	180,19
19,00	178	238,90