


**Cablu tractiune constructie 6x19M-FC inima vegetala**Zincat,
mat

Diametru	Greutate aprox.	Sarcina minima la rupere		
		1570 N/mm ²	1770 N/mm ²	1960 N/mm ²
mm	kg/100m	kN	kN	kN
3,0	3,1	4,34	4,89	5,42
3,5	4,2	5,90	6,66	7,37
4,0	5,5	7,71	8,69	9,63
5,0	8,7	12,0	13,6	15,0
6,0	12,5	17,4	19,6	21,7
7,0	17,0	23,6	26,6	29,5
8,0	22,1	30,8	34,8	38,5
9,0	28,0	39,0	44,0	48,7
10,0	34,6	48,2	54,3	60,2
11,0	41,9	58,3	65,8	72,8
12,0	49,8	69,4	78,2	86,6
13,0	58,5	81,5	91,8	102
14,0	67,8	94,5	107	118
16,0	88,6	123	139	154
17,0	100,0	139	157	174
18,0	112,1	156	176	195
19,0	124,9	174	196	217
20,0	138,4	193	217	241
21,0	152,6	213	240	265
22,0	167,5	233	263	291
23,0	183,0	255	287	318
24,0	199,3	278	313	347



Cablu tractiune constructie 6x19M-IWRC inima metalica

Zincat,
mat

Diametru	Greutate aprox.	Sarcina minima la rupere		
		1570 N/mm ²	1770 N/mm ²	1960 N/mm ²
mm	kg/100m	kN	kN	kN
3,0	3,4	4,69	5,29	5,86
3,5	4,7	6,39	7,20	7,97
4,0	6,1	8,34	9,40	10,4
5,0	9,5	13,0	14,7	16,3
6,0	13,7	18,8	21,2	23,4
7,0	18,7	25,5	28,8	31,9
8,0	24,4	33,4	37,6	41,6
9,0	30,9	42,2	47,6	52,7
10,0	38,1	52,1	58,8	65,1
11,0	46,1	63,1	71,1	78,7
12,0	54,9	75,1	84,6	93,7
13,0	64,4	88,1	99,3	110
14,0	74,7	102	115	128
16,0	97,5	133	150	167
17,0	110,1	151	170	188
18,0	123,4	169	190	211
19,0	137,5	188	212	235
20,0	152,4	208	235	260
21,0	168,0	230	259	287
22,0	184,4	252	284	315
23,0	201,5	276	311	344
24,0	219,5	300	338	375